

CERTIFICATE

No. Z2 084937 0027 Rev. 04


Holder of Certificate:

Canadian Solar Inc.

545 Speedvale Ave West Guelph Ontario N1K1E6

CANADA

Certification Mark:



Product:

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

Poly-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.:

704061612705-10

Valid until:

2024-12-17

Date,

2019-12-18

(Zhulin Zhang)

TÜV®



CERTIFICATE

No. Z2 084937 0027 Rev. 04

Model(s):

CS6U-xxxP (xxx=255 to 375 in step of 5W) CS6X-xxxP (xxx=255 to 350 in step of 5W) CS6U-xxxP-WS (xxx=255 to 350 in step of 5W) CS6X-xxxP-WS (xxx=255 to 350 in step of 5W) CS6K-xxxP (xxx=200 to 310 in step of 5W) CS6P-xxxP (xxx=200 to 285 in step of 5W) CS6K-xxxP-SD (xxx=200 to 285 in step of 5W) CS6P-xxxP-SD (xxx=200 to 285 in step of 5W) CS6K-xxxP-WS (xxx=200 to 285 in step of 5W) CS6P-xxxP-WS (xxx=200 to 285 in step of 5W) CS6X-xxxP-FG (xxx=290 to 350 in step of 5W) CS6X-xxxP-FG1 (xxx=290 to 350 in step of 5W) CS6K-xxxP-FG (xxx=245 to 300 in step of 5W) CS6K-xxxP-FG1 (xxx=245 to 300 in step of 5W) CS6K-xxxP-FG3 (xxx=245 to 300 in step of 5W) CS3U-xxxP (xxx=310 to 385 in step of 5W) CS3K-xxxP (xxx=250 to 320 in step of 5W) CS3U-xxxP-FG (xxx=310 to 385 in step of 5W) CS3K-xxxP-FG (xxx=250 to 320 in step of 5W) CS3K-xxxP-FG1 (xxx=250 to 320 in step of 5W) CS3W-xxxP (xxx=380 to 445 in step of 5W) CS3L-xxxP (xxx=315 to 365 in step of 5W) CS3U-xxxPB-FG (xxx=320 to 420 in step of 5W) CS3U-xxxPB-AG (xxx=320 to 420 in step of 5W) CS3K-xxxPB-FG (xxx=265 to 350 in step of 5W) CS3K-xxxPB-AG (xxx=265 to 350 in step of 5W) CS6K-xxxPB-FG (xxx=255 to 300 in step of 5W) CS3W-xxxPB-AG (xxx=385 to 445 in step of 5W) CS3U-xxxP-AG (xxx=320 to 385 in step of 5W) CS3L-xxxPB-AG (xxx=320 to 365 in step of 5W) CS3K-xxxP-AG (xxx=265 to 320 in step of 5W) xxx is standing for rated output power at STC

Parameters:

Construction:

Framed or frameless, with Junction box.

Cable and Connectors

Application Class:

Class A

Maximum System Voltage:

1000 V DC or 1500 V DC Class C or Class A

Fire Safety Class:

-1000 V or -1500 V or +1500V.

PID Test Condition:

96 Hours, 85 °C, 85 % RH

PID testing method is according to IEC TS 62804-1:2015

Tested

IEC 61215(ed.2)

according to:

IEC 61730-1(ed.1);am1;am2 IEC 61730-2(ed.1);am1

PPP 58042B:2015

Production Facility(ies): 084938

